## Amendments to the Claims:

## Claims 1-5 (canceled)

6. (New) A portable computer device comprising:

a computer main unit having a mounting section therein including a space, said mounting section being provided with a first terminal section and a locking mechanism; and

a loudspeaker unit detachably lockable in said mounting section of said computer main unit by said locking mechanism;

wherein said loudspeaker unit includes a second terminal section for connecting with said first terminal section and exchanging power and sound information signals with said computer main unit; and

wherein said loudspeaker unit further includes an acoustic space and a port for reproducing low-audio frequencies.

- 7. (New) The portable computer device as claimed in claim 6, wherein said loudspeaker unit further includes a built-in amplifier.
- 8. (New) The portable computer device as claimed in claim 6, wherein said first terminal section has a power supply terminal for connection to at least one of said loudspeaker unit and a rechargeable battery.
- 9. (New) The portable computer device as claimed in claim 6, wherein said first terminal section comprises a plurality of terminals to provide for connection to said second terminal section and to a terminal of a rechargeable battery.
  - 10. (New) The portable computer device as claimed in claim 6, wherein



said first terminal section comprises a plurality of terminals.

11. (New) The portable computer device as claimed in claim 6, wherein said port comprises an elongated chamber formed in said loudspeaker unit and arranged such that, when said loudspeaker unit is received in said mounting section of said computer main unit with said first terminal section connected with said second terminal section, said port opens to an exterior of said computer main unit.

12. (New) The portable computer device as claimed in claim 6, wherein said port is formed in said loudspeaker unit such that, when said loudspeaker unit is received in said mounting section of said computer main unit with said first terminal section connected with said second terminal section, said port opens to an exterior of said computer main unit.